

WHAT IS CLAIMED IS:

1 1. A method comprising:
2 receiving information about a recognized phrase from
3 a speech engine; and
4 selecting, based on the recognized phrase, a handler
5 function from sets of handling information, each set of
6 handling information being associated with a different
7 application.

1 2. The method of claim 1, further comprising:
2 identifying an application that is a focus of the
3 recognized phrase, selecting the handler function being
4 further based on the identified application.

1 3. The method of claim 2 wherein selecting a handler
2 function comprises:
3 selecting a set of handling information based on the
4 identified application; and
5 selecting a handler function from the selected set
6 of handling information based on the recognized phrase.

1 4. The method of claim 3 further comprising, prior to
2 receiving the recognized phrase:
3 locating the sets of handling information.

1 5. The method of claim 4 wherein each of the sets of
2 handling information is located when the execution of the

associated application is initiated.

6. The method of claim 4 further comprising:
detecting a change of the focus from a first
application to a second application;
producing a second grammar based on the handling
information associated with the second application; and
loading the second grammar onto the speech engine.

7. The method of claim 6 further comprising:
generating an uncompiled grammar based on the
handling information; and
compiling the grammar into a binary format.

8. The method of claim 6 further comprising, prior to
the step of loading the second grammar:
unloading a first grammar associated with the first
application from the speech engine.

9. The method of claim 6 further comprising:
directing an operating system to provide
notification in response to the focus changing;
wherein the step of determining when the focus
changes includes receiving notification from an operating
system.

10. The method of claim 5 further comprising:
directing an operating system to provide
notification whenever the execution of an application is

initiated;

wherein each set of handling information is located
when the notification is provided.

11. The method of claim 6 further comprising:

storing the produced grammar; and
loading the stored grammar onto the speech engine
when the focus is changed from a third application to the
second application.

12. An article comprising a machine-readable medium
which stores machine-executable instructions, the
instructions causing a machine to:

receive information about a recognized phrase from a
speech engine; and

select, based on the recognized phrase, a handler
function from sets of handling information, each set of
handling information being associated with a different
application.

13. The article of claim 12, wherein the instruction
further cause the machine to:

identify an application that is a focus of the
recognized phrase, selecting the handler function being
further based on the identified application.

14. The article of claim 13 wherein selecting a handler
function comprises:

selecting a set of

4 handling information based on the identified application;
5 and

6 selecting a handler function from the selected set
7 of handling information based on the recognized phrase.

1 15. The article of claim 14 wherein the instructions
2 further cause the machine, prior to receiving the
3 recognized phrase, to:

4 locate sets of handling information, each of the
5 sets of handling information being associated with a
6 different application.

1 16. The article of claim 15 wherein each of the sets of
2 handling information is located when the execution of the
3 associated application is initiated.

1 17. The article of claim 15 wherein the instructions
2 further cause the machine to:

3 detect a change of the focus from a first
4 application to a second application;

5 produce a second grammar based on the handling
6 information associated with the second application; and

7 load the second grammar onto the speech engine.

1 18. The article of claim 14 wherein the instructions
2 further cause the machine to:

3 generate an uncompiled grammar based on the handling
4 information; and

5 compile the grammar into a binary format.

1 19. The article of claim 17 wherein the instructions,
2 prior to the step of loading the second grammar, further
3 cause the machine to:

4 unload a first grammar associated with the first
5 application from the speech engine.

1 20. The article of claim 17 wherein the instructions
2 further cause the machine to:

3 direct an operating system to provide notification
4 in response to the focus changing;

5 wherein the step of determining when the focus is
6 changed includes receiving notification from an operating
7 system that the focus has been changed.

1 21. The article of claim 16 wherein the instructions
2 further cause the machine to:

3 direct an operating system to provide notification
4 whenever the execution of an application is initiated;

5 wherein each set of handling information is located
6 when the notification is provided

1 ~~22.~~ An apparatus comprising:

2 a memory which stores computer readable instructions;

3 a processor which executes the computer readable
4 instructions, the instructions causing the processor to:

5 receive information about a recognized phrase from a
6 speech engine;

7 identify an application that is a focus of the
8 recognized phrase; and

9 select a handler function based on the recognized
10 phrase and the application that is the focus of the
11 phrase.

1 23. The apparatus of claim 22 wherein selecting a
2 handler function comprises:

3 selecting a set of handling information based on the
4 identified application; and

5 selecting a handler function from the selected set
6 of handling information based on the recognized phrase.

7 24. The apparatus of claim 23 wherein the instructions
8 further cause the processor, prior to receiving the
9 recognized phrase, to:

10 locate sets of handling information, each of the
11 sets of handling information being associated with a
12 different application.

1 25. The apparatus of claim 24 wherein each of the sets
2 of handling information is located when the execution of
3 the associated application is initiated.

1 26. The apparatus of claim 24 wherein the instructions
2 further cause the processor to:

3 detect a change of the focus from a first
4 application to a second application;
5 produce a second

6 grammar based on the handling information associated with
7 the second application; and

8 load the second grammar onto the speech engine.

1 27. The apparatus of claim 23 wherein the instructions
2 further cause the processor to:

3 generate an uncompiled grammar based on the handling
4 information; and

5 compile the grammar into a binary format.

1 28. The apparatus of claim 26 wherein, prior to the step
2 of loading the second grammar, the instructions further
3 cause the processor to:

4 unload a first grammar associated with the first
5 application from the speech engine.

1 29. The apparatus of claim 26 wherein the instructions
2 further cause the processor to:

3 direct an operating system to provide notification
4 in response to the focus changing;

5 wherein the step of determining when the focus is
6 changed includes receiving notification from an operating
7 system that the focus has been changed.

1 30. The apparatus of claim 25 wherein the instructions
2 further cause the processor to:

3 direct an operating system to provide notification
4 whenever the execution of an application is initiated;

5 wherein each set of

6 handling information is located when the notification is
7 provided.

1

093433-04201